PATENT ABSTRACTS OF JAPAN

(11)Publication number:

2004-266339

(43)Date of publication of application: 24.09.2004

(51)Int.CI.

HO4B 10/02 HO4B 10/18

(21)Application number: 2003-023973

(71)Applicant: JAPAN SCIENCE & TECHNOLOGY

AGENCY

(22)Date of filing:

31.01.2003

(72)Inventor: HIROOKA TOSHIHIKO


NAKAZAWA MASATAKA

(54) OPTICAL TRANSMISSION METHOD AND DEVICE (57) Abstract:

PROBLEM TO BE SOLVED: To compensate waveform distortion by using characteristic that, even if every linear distortion occurs on a time base, a spectrum

shape is perfectly preserved.

SOLUTION: An optical pulse which has been transmitted via an optical fiber transmission path 2 from an optical pulse transmitter 1 is transmitted. An optical Fourier transforming device 3 compensates the waveform distortion by linear effects in the optical fiber transmission path 2 by making the optical pulse incident, performing optical Fourier transformation with the optical pulse on the time base onto a frequency axis, replacing frequency with time, and reproducing the frequency spectrum of the optical pulse on the time base. A photodetector 4 obtains the pulse waveform before transmission by the optical fiber transmission path 2 by receiving the optical pulse from the optical Fourier transforming device 3 and transforming this to an electrical signal.



LEGAL STATUS

[Date of request for examination]

14.02.2005

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]